

WT-CCM-1200 Welding table



Description

WT-CCM-1200 is a complete welding working station that effectively captures and filters the welding fumes generated during welding operations. WT-CCM-1200 is designed for fumes extraction during MIG/MAG welding processes or inert gas welding with consumable electrodes. Unit is equipped with built-in filter cleaning system that requires connection to external compressed air supply. WT-CCM-1200 unit is suitable for continuous indoor operation under the following environmental conditions: ambient temperature from +10 to +45 °C and relative humidity of 80% at 25 °C.

Applications

- Welding processes

Features

- Built-in silencer
- Steel working surface with integrated extraction aluminium grate
- Built-in filter cleaning system
- Openable side screens, large parts handling
- Equipped with turntable for small parts
- Compatible with different types of filter cartridges

Restrictions

- Not suitable for thermal metal cutting applications
- Not suitable for operation in the presence of explosive dust or aerosols or aggressive vapors and gazes

Technical characteristics

Weight allowance, kg	Height of the table surface, mm	Max airflow, m ³ /h	Power consumption (380V), kW	Built-in fan type	Filter surface (depends on cartridge type), m ²	Noise level, dB	Weight, kg
100	815	1200	1,2	VM-p2500	12/10	70	200

Article numbers


Article №	Model	Cartridge type
27849	WT-CCM-1200-T10	Tcart-10
27843	WT-CCM-1200-T12	Tcart-12

Delivery set / Standard kit info

- Built-in fan
- Filter cartridge of respective type
- Extraction arm
- Steel back and side protective screens
- Turntable for small parts
- Oil and moisture separator with reducer for compressed air



Spare filter elements

	Article №	Model	Description
	6908	Tcart-10	Spare filter cartridge, 10 m ² , PTFE
	6903	Tcart-12	Spare filter cartridge, 12m ² , PTFE

